

Resettable Analogue LHDC 1m Portable Test Oven



Commissioning and routine maintenance testing of the Patol Resettable Analogue Linear Heat Detection Cable systems can be conducted at site by the use of a calibrated One Metre Test Oven.

The portable One Metre Test Oven concept of testing, allows accessible one metre installed lengths of sensor cable to be subjected to temperatures within the Alarm range. Thus confirming correct calibration setting selection and Alarm levels in accordance with project specification requirements.

Where sensor cable is installed within hazardous classified areas or may be inaccessible for oven use, an additional one metre length may be 'series' wired with existing cable (sensor and / or interconnecting cables) to allow testing to be carried out local to the electronic interface unit (in the safe area). Without adversely affecting system performance levels.

Specification

Dimensions:	1120 x 145 x155mm
Weight:	15kg
Operating Voltage:	230/115 Vac (fuse rated 10A)
Temperature Range:	0°C to 200°C
Outer Case:	Ruggedised Aluminium

Ordering Information

Description	Part Number
1m Test Oven	700-000

For use with the following cables and controllers:

Red FRPE	700-001LS0H
Red FRPE S.S*	700-005LS0H

Red PVC (Legacy)	700-001
Red PVC S.S* (Legacy)	700-005
Black Nylon (Legacy)	700-003
Black Nylon S.S* (Legacy)	700-004

*Stainless Steel Braid

LDM-519-LP	700-201
LDM-519-SEN-N	700-305
LDM-519-ACT-N	700-304